



注意: 孔位分布图以SHF-32为例, 需要详细图纸请联系博盈轴承;
 Notice: Holes locations in the drawing is SHF-32, need detail drawings please contact BYC bearings;

交叉滚子轴承配套用于SHF/SHG型谐波减速机 (Cross Roller Bearing used for SHF/SHG Harmonic Drive)

轴承型号 Model Number		基本尺寸 Main Dimension (mm)											内圈安装孔 Holes Of Inner Ring			外圈安装孔 Holes Of Outer Ring			额定载荷 Load Rating (KN)		重量 Weight
													中心径	内圈孔la	内圈孔lb	中心径	外圈孔Oa	外圈孔Ob			
博盈型号 BYC Model	互换型号 Interchange Model	d	D	H	H1	d1	d2	d3	d4	dp	b	b1	P1	la	lb	P2	Oa	Ob	C	Co	Kg
BSHF(BSHG)-14	CRU14-70	35.6	70	15.1	14.1	38	53.3	56.5	0.9	51	5	5	44	12-M3-深5	-	64	8-Φ3.5	2-M3-深5	5.8	8.6	0.3
BSHF(BSHG)-17	CRU17-80	44.1	80	17	16	47	64.1	68.1	1.1	61.5	6.5	5	54	20-M3-深5	-	74	12-Φ3.5	4-M3-深5	10.4	16.3	0.44
BSHF(BSHG)-20	CRU20-90	51.3	90	18.5	17.5	54	72.6	78	1.5	71	7	5	62	16-M3-深6	4-M3-深6	84	12-Φ3.5	4-M3-深6	14.6	22	0.59
BSHF(BSHG)-25	CRU25-110	64.2	110	20.7	18.7	68	90	94.8	1.4	86	7.5	5	77	16-M4-深8	4-M3-深6	102	12-Φ4.5	4-M3-深6	21.8	35.8	0.9
BSHF(BSHG)-32	CRU32-142	84	142	24.4	23.4	88	117.6	123	1.5	112	8	6	100	16-M5-深8	4-M4-深8	132	12-Φ5.5	4-M4-深8	38.2	65.4	1.87
BSHF(BSHG)-40	CRU40-170	106	170	30	29	108	142.6	148	1.5	134.5	9.5	7	122	16-M6-深10	4-M5-深10	158	12-Φ6.6	6-M4-深8	43.3	81.6	3.1
BSHF(BSHG)-50	CRU50-214	129	214	36	34	135	182.6	188	1.5	172	11	8	154	16-M8-深12	8-M5-深12	200	12-Φ9	6-M5-深10	81.6	149	6

C : Basic Dynamic Rated Load

Co : Basic Static Rated Load

Basic dynamic rated load is a constant radial load where the basic dynamic rated life of Cross Roller Bearing is 1000x1000 rotations .

Basic static rated load is a static load where the value of moment rigidity is the average value .